



ИГП-114

ИГП-18, ИГП-30, ИГП-38, ИГП-49, ИГП-72, ИГП-114 - индустриални легирани масла, използвани в хидравлични системи на машини, преси, автоматични линии на индустриално оборудване, където се изискват масла с подобрени антиоксидантни и противоизносни свойства. ИГП-152 - масло индустриално легирано, предназначено за смазване на заредени зъбни и червячни зъбни колела, редуктори на оборудване, работещо в предприятията на металургичната, целулозно-хартиената промишленост. Маслата се произвеждат от минерални масла чрез дълбоко селективно почистване и прибавяне на добре балансиран пакет от добавки.

Advantages

Physico-chemical characteristics

Indicator	Method	ИГП-114
Kinematic Viscosity at 40 °C, mm ² /s	ГОСТ 33	195.2
Flash Point (COC), °C	ГОСТ 4333	256
Pour Point, °C	ГОСТ 20287	- 17
Total Acid Number, mg KOH/g	ГОСТ 11362	0.8
Sulfated Ash, wt%	ГОСТ 1461	0.12
Density at 20 °C, kg/cm ³	ASTM D 4052	895
Viscosity Index	ГОСТ 25371	88
Color of colorimeter CNT with dilution 15:85, unit CNT	ГОСТ 20284	4.0

The company's management system is certified in accordance with international standards

ISO 9001



ISO 14001



ISO/TS 16949



OHSAS 18001



Gazpromneft — Lubricants Ltd.
117218, Moscow, 14/3 Krzhizhanovski
Str., Block A
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63

The above data are typical for the current production. Due to continuous research and development, the information provided in the document may be changed.
Information on the safe use of the product is contained in the Safety Data Sheet. You can get more detailed information from the technical specialists of the company.
E-mail: service@maslagaz.com 01/2018