



Gazpromneft GL-5 90



Висококачествени минерални базови масла



Водещи мостове



Нискотемпературни свойства



Отлични противозадирни свойства

Трансмисионните масла Gazpromneft GL-5 75W-90 (полусинтетични), 80W-90, 90, Gazpromneft Super T-3, SAE 85W-90 (минерални) са предназначени за използване в трансмисионни агрегати, подложени на големи натоварвания (главна трансмисия, задвижващи оси), където е необходима производителност на API GL-5. Маслата ефективно предпазват хипоидните части на зъбните колела от износване. Gazpromneft GL-5 90 е специално създадено за райони с горещ климат. Маслото Gazpromneft GL-5 75W-90 е с подобрени свойства при ниски температури и удължен експлоатационен живот в сравнение с маслата на минерална основа.

Advantages

Application



Physico-chemical characteristics

Indicator	Method	Gazpromneft GL-5 90
Kinematic Viscosity at 100 °C, mm ² /s	ASTM D 445	17.0
Flash Point (COC), °C	ASTM D 92	234
Pour Point, °C	ГОСТ 20287	- 17
Density at 20 °C, g/cm ³	ASTM D 4052	895
Tribological characteristics, Four-Ball Method Load-wear index, N Weld point, N	ГОСТ 9490 ГОСТ 9490	572 4250

Specifications

- SAE 90
- API GL-5

The company's management system is certified in accordance with international standards

ISO 9001



ISO 14001



ISO/TS 16949



OHSAS 18001



Gazpromneft — Lubricants Ltd.
117218, Moscow, 14/3 Krzhizhanovski
Str., Block A
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63

The above data are typical for the current production. Due to continuous research and development, the information provided in the document may be changed.
Information on the safe use of the product is contained in the Safety Data Sheet. You can get more detailed information from the technical specialists of the company.
E-mail: service@maslagaz.com 01/2018