

Safety Data Sheet G-ENERGY SERVICE LINE W 5W-40

Safety Data Sheet dated 7/9/2015 version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: G-ENERGY SERVICE LINE W 5W-40

Trade code: FO000038 Registration Number N/A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Gasoline or diesel engine oil for passenger cars

Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Gazpromneft Lubricants Italia SpA

Via Bitritto km 7,800

70124 Bari

1.4. Emergency telephone number

1-760-476-3962 (America)

1-760-476-3961 (Europe, Middle East and Africa)

1-760-476-3960 (Asia Pacific)

Global Response Access Code: 333497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH210 Safety data sheet available on request.

Ingredient(s) with unknown acute toxicity:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT Ingredients are present

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: G-ENERGY SERVICE LINE W 5W-40

Hazardous components within the meaning of the CLP regulation and related classification:

Quantity Name Ident. Numb. Classification Registration Number Properties:

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 1 of 7

40-50 %	DISTILLATES(PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL UNSPECIFIED	CAS:64742-54-7 EC:265-157-1	Asp. Tox. 1, H304	01-2119484627-25
1-5 %	REACTION PRODUCTS OF BENZENEAMINE, N-PHENYL-WITH NONENE (BRANCHED)	EC:253-249-4	Aquatic Chronic 4, H413	01-2119488911-28
0.1-1 %	PHOSPHORODITHIOIC ACID, MIXED O, O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR)ESTERS, ZINC SALTS	EC:283-392-8	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aqu Chronic 2, H411	atic 01-2119493626-26
0.1-1 %	ZINC O,O,O',O'-TETRAKIS(1, 3-DIMETHYLBUTYL) BIS(PHOSPHORODITHIOATE)	EC:218-679-9	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aqu Chronic 2, H411	atic 01-2119953275-34
0.1-1 %	DIPHENYLAMINE	EC:204-539-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the MSDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

Not known

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Do not eat or drink while working.

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 2 of 7

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL(A.C.G.I.H. 2008): oil mists - TLV/TWA (8 h): 5 mg/m3 - TLV/STEL: 10 mg/m3

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
DIPHENYLAMINE	EU	AUSTRIA			0.700		1.400		

8.2. Exposure controls

Material should be handled in enclosed vessels and equipment, in which case general (mechanical) room ventilation should be sufficient. Local exhaust ventilation or adequate ventilation should be used at points where dust, mist, vapors or gases can escape into the room air.

Eye protection:

Safety Glasses.

Protection for skin:

Protection for hands:

Use nitrile or neoprene gloves. Long sleeve shirt is recommended. Wear a chemically protective when contact with material may occur. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Launder contaminated clothing before reuse.

Not needed for normal use.

Respiratory protection:

Use in ventilated area. Use respirator with a combination organic vapor and high efficiency filter cartridge just if recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites

Hygienic and Technical measures

Wash thoroughly after handling this product. Do not eat, drink or smoke when using this product.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Oily brown

Odour: characteristic Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: 230 °C (446 °F) (ASTM D92 (Cleveland Open Cup))

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A.

Relative density: 853.00 kg/m3 (ASTM D4052 @ 15°C)

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Kinematic Viscosity at 100°C: 13.00 mm2/s (ASTM D445) Kinematic Viscosity at 40°C (mm2/s): Kv > 20.5 (ASTM D445)

Dinamic Viscosity: N.A.

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 3 of 7

Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.

Volatile Organic compounds - VOCs = N.A.

9.2. Other information

Substance Groups relevant properties N.A.

Miscibility: N.A. Conductivity: N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Carefully review all information provided in sections 10.2 - 10.6.

10.2. Chemical stability

Material is normally stable at room temperature and pressure. See Section 7 for further details.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Do not expose to excessive heat, ignition sources, or oxidizing materials. Avoid contact with strong caustic agents.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Other potential decomposition products: sulfur acids.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Products have not been tested. Evaluation has been made through data of components.

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

DIPHENYLAMINE

a) acute toxicity

ATE Oral 100.00000mg/kg

ATE 300.00000mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Carcinogenicity

This product contains mineral oils which are severely refined and not considered to be carcinogenic under IARC. All components in this product have been passed the test IP346 (DMSO extractible compounds less than 3%).

Skin corrosion / irritation

Avoid direct contact. Repeated or prolonged skin contact may cause irritation. Contact with heated product may cause thermal burns. Based on data from components or similar materials.

Serious eye damage / irritation

Vapors may cause eye damage/irritation. Evaluation is based on data from components or similar materials.

Respiratory Irritation

If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components or similar materials.

Respiratory or skin sensitization

Skin

Products have not been tested. Evaluation has been made through data of components.

Respiratory

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 4 of 7

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

No Data Available

12.2. Persistence and degradability

NΑ

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

ΝΔ

Product floats on water (insoluble) and can entrape small organisms. The product could easily disperse in soil.

Products have not been tested. Evaluation has been made through data of components.

12.5. Results of PBT and vPvB assessment

No PBT Ingredients are present

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N.A.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

14.6. Special precautions for user

N.A

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 5 of 7

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU)2015/830

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

German Water Hazard Class.

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None

Restrictions related to the substances contained:

15.2. Chemical safety assessment

Chemical Safety Assessment: No

SECTION 16: Other information

Code	Description
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H373	$\label{eq:mage_energy} \mbox{May cause damage to organs through prolonged or repeated exposure} \; .$
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 6 of 7

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep away from heat KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Date 7/9/2015 Production Name G-ENERGY SERVICE LINE W 5W-40 Page n. 7 of 7